

FTB

ARTE MUNDIT®

ODOURLESS

ART NR 90.100-106

ODOURLESS CREAM-PASTE FOR DUST-FREE DRY INTERIOR CLEANING

DESCRIPTION

ARTE MUNDIT® IS AN ODOURLESS DRY CLEANSING PASTE FOR INTERIOR CLEANING, TO REMOVE POLLUTION AND DUST FROM ALL KIND OF SUPPORTS: TO REMOVE DUST, SOOT, NICOTINE DEPOSIT AND OTHER POLLUTION FROM INTERIOR WALLS, CEILINGS, FLOORS, STUCCO, NATURAL STONE, MARBLE, CONCRETE, BRICKS, PLASTER, GYPSUM STATUES, POLISHED WOOD, SYNTHETIC MATERIALS, ETC.

ADVANTAGES

- EXISTING SALTS ARE NOT DISSOLVED AGAIN IN THE STONE MASS
- NO NUISANCE BY WATER, SO:
- NO RISKS FOR UNDERLYING WORKS OF ART
- NO RISKS FOR STAINING
- NO FORMATION OF MILDEW
- THE PORES ARE ALSO CLEANED
- THE DEEPER PROFILES ARE ALSO CLEANED
- NO CHEMICAL AFTER-EFFECT
- USER-FRIENDLY
- NO ATTACKS ON GYPSUM RESTORATIONS
- HIGH PERFORMANCE, CAN BE SPRAYED WITH A MACHINE.

PROCEDURE OF APPLICATION

PREPARATION OF THE SUPPORT:

VACUUM ALL SUPPORTS INCLUDING MOULDINGS, CARVED STONWORK AND THE FLAT AREAS OF THE WALL.

MASK OFF GILDED, PAINTED, GLASS OR METAL FITTINGS WITH A LIGHT DUTY POLYETHYLENE. PROTECT DOORS, WINDOWS, MONUMENTS AND OTHER FRAGILE ITEMS WITH HEAVY DUTY GRADE POLYETHYLENE. CAREFULLY TAPE TO SEAL PROTECTION COMPLETELY AND TO PREVENT THE INGRESS OF WATER, CLEANING FLUIDS, DUST OR DEBRIS.

THE AREA TO BE CLEANED SHOULD BE DRY AND FREE FROM DUST AND LOOSE DEBRIS.

APPLICATION:

ARTE MUNDIT® IS READY FOR USE. NEVER DILUTE THE PRODUCT. ARTE MUNDIT® SHOULD BE MIXED VERY WELL BEFORE APPLYING WITH A PAINT BRUSH OR A SPECIALLY DEVELOPED SPRAYING MACHINE (PUMP).

ENSURE THAT THE PRODUCT FORMS A CONTINUOUS FILM AND THAT IN CARVED AREAS IT IS PROPERLY APPLIED TO ALL DETAILS REACHING ALL CREVICES. TAKE THE PACK OVER THE EDGES OF THE PROTECTIVE POLYETHYLENE TO ENSURE A COMPLETELY WATERPROOF SEAL AROUND THE BORDERS OF THE AREA.

THE POLYMERISED FILM IS NOT DANGEROUS FOR THE ENVIRONMENT EXCEPT IF IT CONTAINS TOXIC STAINS.

DO NOT APPLY ON HOT SURFACES.

IT IS RECOMMENDED TO USE STAINLESS TOOLS OR SYNTHETIC MATERIAL.

REMOVAL:

THE ARTE MUNDIT® TAKES UP TO 24 HOURS TO CURE DEPENDING UPON THICKNESS OF APPLICATION AND ATMOSPHERIC CONDITIONS.

20°C (68°F) – 40% R.H.: 3 HOURS	10°C (50°F) – 65% R.H.: 22 HOURS
20°C (68°F) – 65% R.H.: 3 HOURS	20°C (68°F) – 65% R.H.: 3 HOURS
20°C (68°F) – 95% R.H.: 22 HOURS	30°C (86°F) – 65% R.H.: 2,5 HOURS
5°C (41°F) – 65% R.H.: 23 HOURS	

PEEL BACK THE CURED EXPOSING ONLY A SURFACE LARGE ENOUGH TO BE WASHED DOWN WITHIN 1 HOUR. ARTE MUNDIT® TYPE I NEVER NEEDS WASHING DOWN. WHEN REMOVING THE PACK FROM AREAS OF CARVED STONWORK, PARTICULAR CARE MUST BE TAKEN TO PEEL THE PACK BACK GENTLY, CUTTING IT WHERE NECESSARY TO REDUCE TENSION.

CLEAN DOWN FROM THE HIGHEST POINT USING A LITTLE WATER AND SPONGES. WHERE NECESSARY MEDIUM NYLON BRISTLE BRUSHES WILL BE USED TO CLEAN MORE INTENSIVELY. CARE SHOULD BE TAKEN TO USE AS LITTLE WATER AS POSSIBLE.

CLEANING OF THE MATERIAL

WITH COLD WATER AND/OR LIQUID SOAP OR PEELING AFTER COMPLETE POLYMERISATION.

TYPES

ARTE MUNDIT[®] ODOURLESS IS AVAILABLE IN A NUMBER OF DIFFERENT TYPES DEPENDING ON THE SURFACE (MARBLE, NATURAL STONE, BRICK, CONCRETE, CEMENT OR PLASTER) AND THE DEGREE OF POLLUTION.

ARTE MUNDIT[®] TYPE I IS A DISPERSION OF MODIFIED RUBBER (CONTAINS ALMOST NO AMMONIA < 0,005 %). DURING THE APPLICATION THE AMMONIA WILL EVAPORATE IMMEDIATELY AND THEREFORE WILL HAVE NO HARMFUL INFLUENCE ON THE TREATED SURFACE.

ARTE MUNDIT[®] TYPE II, III AND V CONTAIN A VARIABLE CONCENTRATION OF COMPLEXES. THE MIXTURE CONTAIN A NUMBER OF ADDITIVES NECESSARY TO ENSURE THE LONG TERM STABILITY, TO ADAPT THE CURE TIME TO THE SPECIFIC WORKING CONDITIONS. NONE OF THESE CHEMICAL ADDITIVES CAN REACT ON THE SURFACE, THEY EVAPORATE DURING THE CURE PROCESS OR ARE ATTACHED IN THE DRY FILM. THE MANUFACTURER DETERMINES WHICH TYPE OF ARTE MUNDIT[®] WILL BE APPLIED, DEPENDING ON THE DEGREE OF POLLUTION.

CONSUMPTION

ON FLAT SURFACE: 0,7 - 1,0 KG/M² (0.143 – 0.205 LBS/FT²)

ON CARVED SURFACE: 1,0 - 3,0 KG/M² (0.205 – 0.614 LBS/FT²)

DENSITY: +/- 0,94 – 0,99 KG/LTR

+/- 7.845 – 8.262 LBS/GALLON (US)

+/- 9.421 – 9.922 LBS/GALLON (UK)

CONDITIONING

15 KG (+/- 33 LBS).

STORAGE TIME

MAXIMUM 1 YEAR IN CLOSED CONDITIONING AND FROST-FREE.

PRECAUTIONS

AVOID CONTACT WITH THE SKIN. CAREFULLY WASH HANDS WITH WATER AND SOAP BEFORE SMOKING OR EATING.

ENSURE A GOOD VENTILATION DURING THE PREPARATION AND THE APPLICATION OF THE PRODUCT.

EPILOGUE

OUR TECHNICAL INFORMATION IS BASED ON OUR OWN EXPERIENCE AND IS GIVEN IN GOOD FAITH. WE GUARANTEE A CONSTANT QUALITY OF OUR PRODUCTS, BUT WE CANNOT ACCEPT ANY RESPONSIBILITY CONCERNING THEIR APPLICATION.